



SGS-CSTC Standards Technical Services Co., Ltd. Guangzhou Branch

198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM170400213101

Page: 1 of 23

TEST REPORT

Application No.: GZEM1704002131HS
Applicant: ZHEJIANG CHONG BO SCIENCE & TECHNOLOGY CO., LTD
Address of Applicant: NO. 32 Jiuding Road Yongkang City Zhejiang Province
Manufacturer: the same as applicant
Address of Manufacturer: the same as applicant
Factory: the same as applicant
Address of Factory: the same as applicant
Equipment Under Test (EUT):
EUT Name: Counter
Model No.: CB-TP010, CB-TP003, CB-TP004, CB-TP005, CB-TP006, CB-TP007, CB-TP008, CB-TP009, CB-TP011, CB-TP012, CB-TP013, CB-TP015, CB-TP016, CB-TP017, CB-TP018, CB-TP025, CB-TP026, CB-TP027, CB-TP028, CB-TP029, CB-TP030, CB-JP001, CB-JP002, CB-JP003, CB-JP004, CB-JP005, CB-JP006, CB-JP007, CB-JP008, CB-JP057, CB-JP020, CB-JP056, CB-JP058, CB-JP059, CB-JP060, CB-JP032, CB-JP034, CB-JP040. □
□ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Standards: EN 55014-1:2006 +A1:2009 +A2:2011
EN 55014-2:2015
Date of Receipt: 2017-04-19
Date of Test: 2017-04-24 to 2017-04-25
Date of Issue: 2017-05-02

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EU Directives.



EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.





SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch

Report No.: GZEM170400213101

Page: 2 of 23

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2017-05-02		Original

Authorized for issue by:			
Tested By			
	Allen_Zhou /Project Engineer	2017-04-24 to 2017-04-25	Date
Checked By			
	Terry_Lai /Reviewer	2017-05-02	Date

2 Test Summary

Emission Part				
Item	Standard	Method	Requirement	Result
Radiated Disturbance (30MHz-1GHz)	EN 55014-1:2006 +A1:2009 +A2:2011	CISPR 16-2-3	N/A	Pass

Immunity Part				
Item	Standard	Method	Requirement	Result
Electrostatic Discharge	EN 55014-2:2015	EN 61000-4-2:2009	4kV Contact Discharge 8kV Air Discharge	Pass
Radiated Immunity (80MHz-1GHz)	EN 55014-2:2015	EN 61000-4-3:2006 +A1:2008+A2:2010	3V/m, 80%, 1kHz Amp. Mod.	Pass

▣ Declaration of EUT Family Grouping:

Model No.: CB-TP010, CB-TP003, CB-TP004, CB-TP005, CB-TP006, CB-TP007, CB-TP008, CB-TP009, CB-TP011, CB-TP012, CB-TP013, CB-TP015, CB-TP016, CB-TP017, CB-TP018, CB-TP025, CB-TP026, CB-TP027, CB-TP028, CB-TP029, CB-TP030, CB-JP001, CB-JP002, CB-JP003, CB-JP004, CB-JP005, CB-JP006, CB-JP007, CB-JP008, CB-JP057, CB-JP020, CB-JP056, CB-JP058, CB-JP059, CB-JP060, CB-JP032

According to the declaration of the applicant, the electrical circuit design, layout, components used and internal wiring were identical for above models, with only difference being the item numbers.

Therefore only one model CB-TP010 was tested in this report.

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	5
4.4 Standards Applicable for Testing	6
4.5 Test Location	7
4.6 Test Facility	8
4.7 Deviation from Standards	8
4.8 Abnormalities from Standard Conditions	8
4.9 Monitoring of EUT for All Immunity Test	9
5 Equipment List.....	10
6 Emission Test Results	12
6.1 Radiated Disturbance(30MHz-1GHz)	12
6.1.1 E.U.T. Operation.....	12
6.1.2 Test Setup Diagram.....	12
6.1.3 Measurement Data	12
7 Immunity Test Results	15
7.1 Performance Criteria Description in EN 55014-2:2015.....	15
7.2 Electrostatic Discharge	16
7.2.1 E.U.T. Operation.....	16
7.2.2 Test Setup Diagram.....	16
7.2.3 Test Results:.....	17
7.3 Radiated Immunity(80MHz-1GHz)	18
7.3.1 E.U.T. Operation.....	18
7.3.2 Test Setup Diagram.....	18
7.3.3 Test Results:.....	19
8 Photographs.....	20
8.1 Radiated Disturbance(30MHz-1GHz) Test Setup	20
8.2 Electrostatic Discharge Test Setup.....	20
8.3 Radiated Immunity(80MHz-1GHz) Test Setup	21
8.4 EUT Constructional Details	22

4 General Information

4.1 Details of E.U.T.

Power Supply: DC 1.5V AAA battery
 Cable: N/A

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

EMC

No.	Item	Measurement Uncertainty
1	Conducted Disturbance Voltage at Mains Terminals	3.63dB (9kHz to 150kHz)
		3.22dB (150kHz to 30MHz)
2	Disturbance Power	3.78dB
3	Radiated Disturbance	5.0dB (30MHz-1GHz)
		5.0dB (1GHz-6GHz)
4	Radiated Immunity	2.18dB(80MHz-3GHz)
5	Conducted Immunity	3.5dB(150kHz-230MHz)
6	ESD	6 %
7	EFT (Electrical Fast Transients)	4 %
8	Surge Immunity	6%
9	Voltage Dips and Interruptions	4 %
10	CISPR 20 Immunity	1.5dB
11	Temperature	0.4 °C
12	Humidity	1.3%
13	DC power	0.5 %

4.4 Standards Applicable for Testing

Table 1 : Tests Carried Out Under EN 55014-1:2006 +A1:2009 +A2:2011

Item	Status
Conducted Disturbance at Mains Terminals(9kHz-30MHz)	×
Radiated Disturbance(30MHz-1GHz)	√
Conducted Disturbance at Mains Terminals(150kHz-30MHz)	×
Conducted Disturbance at Load Terminals and Additional Terminals	×
Discontinuous Disturbance(150kHz-30MHz)	×
Disturbance Power	×
Radiated Disturbance (Magnetic field Induced Current)(9kHz-30MHz)	×

Table 2 : Tests Carried Out Under EN 55014-2:2015

Item	Status
Electrostatic Discharge	√
Radiated Immunity(80MHz-1GHz)	√
Electrical Fast Transients/Burst at Power Port	×
Electrical Fast Transients/Burst at Signal Port	×
Surge at Power Port	×
Conducted Immunity at Power Port(150kHz-80MHz)	×
Conducted Immunity at Signal Port(150kHz-80MHz)	×
Voltage Dips and Interruptions	×
Conducted Immunity at Power Port(150kHz-230MHz)	×
Conducted Immunity at Signal Port(150kHz-230MHz)	×
Electrical Fast Transients/Burst at DC port	×
Conducted Immunity at DC Port(150kHz-80MHz)	×

× Indicates that the test is not applicable
 √ Indicates that the test is applicable

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC (Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co. Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

4.9 Monitoring of EUT for All Immunity Test

Visual: LCD display
Audio: N/A
Other: N/A

5 Equipment List

Radiated Disturbance(30MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver	Rohde & Schwarz	ESIB26	EMC0522	2017-01-20	2018-01-19
EMI Test Receiver	Rohde & Schwarz	ESCI	EMC0056	2017-01-20	2018-01-19
RI High frequency Cable	SGS	20 m	EMC0528	2016-04-19	2018-04-18
Trilog Broadband Antenna 30MHz-1GHz	SCHWARZBECK MESS- ELEKTRONIK	VULB 9160	EMC2025	2016-09-08	2019-09-07
Bi-log Type Antenna	Schaffner -Chase	CBL6112B	EMC0524	2016-09-08	2019-09-07
Bilog Type Antenna	Schaffner -Chase	CBL6143	EMC0519	2014-05-04	2017-05-03
Horn Antenna 1-18GHz	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2016-09-09	2019-09-08
1-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2017-01-20	2018-01-19
Amplifier	HP	8447F	EMC2065	2016-07-04	2017-07-03
PRE AMPLIFIER MH648A	ANRITSU CORP	MH648A	EMC2086	2016-12-02	2017-12-01
Active Loop Antenna	EMCO	6502	EMC0523	2016-02-27	2018-02-26
Broad-Band Horn Antenna (14)15-26.5(40)GHz	SCHWARZBECK MESS- ELEKTRONIK	BBHA 9170	EMC2041	2014-05-26	2017-05-25
High Pass Filter(915MHz)	FSY MICROWAVE	HM1465-9SS	EMC2079	2017-01-20	2018-01-19
2.4GHz filter	Micro-Tronics	BRM 50702	EMC2069	2017-01-20	2018-01-19
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2016-04-30	2018-04-29

Electrostatic Discharge					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
ESD Simulator	TESEQ AG	NSG 435	EMC2071	2017-01-20	2018-01-19
ESD Ground Plane	SGS	3m x 3m	EMC0804	N/A	N/A
Temperature, & Humidity	Shanghai Meteorological Instrument factory Co., Lt	ZJ1-2B	EMC0078	2016-08-18	2017-08-17

Radiated Immunity(80MHz-1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Compact 3m Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	EMC0525	2016-12-04	2019-12-03
Laser probe Interface	Rf Microwave Instrumentation	FI7000	EMC2089	N/A	N/A
Open Switch and control unit	R&S	OSP130	EMC2090	N/A	N/A
Broadband Amplifier (80MHz~1GHz/250W)	R&S	BBA150	EMC2091	2017-01-20	2018-01-19
Broadband Amplifier (800MHz~3GHz/110W)	R&S	BBA150	EMC2092	2017-01-20	2018-01-19
Signal Generator	R&S	SMB100A	EMC2093	2017-01-20	2018-01-19
Laser probe	Rf Microwave Instrumentation	FL7006	EMC2094	2017-01-24	2018-01-23
NRP-Z91 Power Sensor 6GHz	R&S	NPR-Z91	EMC2095	2017-01-20	2018-01-19
NRP-Z91 Power Sensor 6GHz	R&S	NPR-Z91	EMC2096	2017-01-20	2018-01-19
High-Gain Log-preiodic Antenna	R&S	HL046E	EMC2097	2016-02-15	2019-02-14
RI Cable	R&S	7m	EMC2098	2016-05-23	2017-05-22
Oscilloscope	Tektronix	TDS3052C	EMC2055	2017-01-20	2018-01-19
Monitor System	Mitsubish Corp.	M-0552AB	EMC0909	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2016-09-01	2017-08-31
DMM	Fluke	73	EMC0007	2016-09-01	2017-08-31

6 Emission Test Results

6.1 Radiated Disturbance(30MHz-1GHz)

Test Requirement: EN 55014-1:2006 +A1:2009 +A2:2011
 Test Method: CISPR 16-2-3
 Frequency Range: 30MHz to 1GHz
 Measurement Distance: 10m
 Limit:
 30MHz-230MHz 30 dB(μ V/m) quasi-peak
 230MHz-1GHz 37 dB(μ V/m) quasi-peak
 Detector: Peak for pre-scan (120kHz resolution bandwidth) 30MHz to 1000MHz


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1010 mbar

Test mode a:normal working mode.


6.1.2 Test Setup Diagram



6.1.3 Measurement Data

An initial pre-scan was performed in the chamber using the spectrum analyser in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by BiConiLog antenna with 2 orthogonal polarities.


Mode:a; Polarization:Horizontal



Trace: (Discrete)

	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	40.276	22.73	12.82	1.11	27.00	9.66	30.00	-20.34	HORIZONTAL QP
2	61.346	24.15	13.47	1.42	27.00	12.04	30.00	-17.96	HORIZONTAL QP
3	121.549	24.18	11.00	2.11	26.90	10.39	30.00	-19.61	HORIZONTAL QP
4	166.651	23.74	12.93	2.43	26.75	12.35	30.00	-17.65	HORIZONTAL QP
5	392.095	24.66	15.32	3.85	27.12	16.71	37.00	-20.29	HORIZONTAL QP
6	744.866	25.43	21.48	5.39	28.00	24.30	37.00	-12.70	HORIZONTAL QP

Mode:a; Polarization:Vertical



7 Immunity Test Results

7.1 Performance Criteria Description in EN 55014-2:2015

- | | |
|--------------------|---|
| Criterion A | The apparatus shall continue to operate as intended during the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and from what the user may reasonably expect from the apparatus if used as intended. |
| Criterion B | The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level (or permissible loss of performance) specified by the manufacturer, when the apparatus is used as intended. During the test, degradation of performance is allowed, however. No change of actual operating state or stored data is allowed. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation and from what the user may reasonably expect from the apparatus if used as intended. |
| Criterion C | Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls, or by any operation specified in the instructions for use. |

7.2 Electrostatic Discharge


Test Requirement: EN 55014-2:2015
 Test Method: EN 61000-4-2:2009
 Performance Criterion: B
 Discharge Impedance: 330Ω/150pF
 Number of Discharge: Minimum 10 times at each test point
 Discharge Mode: Single Discharge
 Discharge Period: 1 second minimum

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 55 % RH Atmospheric Pressure: 1010 mbar
 Test Mode: a:normal working mode.
 b:idle mode.

7.2.2 Test Setup Diagram



7.2.3 Test Results:

Observations: Test Point:

1. All insulated enclosure and seams.
2. All accessible metal parts of the enclosure.
3. All side

Discharge type	Level (kV)	Polarity	Test Point	Result / Observations
Air Discharge	8	+	1	A
Air Discharge	8	-	1	A
Contact Discharge	4	+	2	A
Contact Discharge	4	-	2	A
Horizontal Coupling	4	+	3	A
Horizontal Coupling	4	-	3	A
Vertical Coupling	4	+	3	A
Vertical Coupling	4	-	3	A

Results:

A: No degradation in the performance of the EUT was observed.

7.3 Radiated Immunity(80MHz-1GHz)

Test Requirement: EN 55014-2:2015
 Test Method: EN 61000-4-3:2006 +A1:2008+A2:2010
 Performance Criterion: A
 Frequency Range: 80MHz to 1GHz
 Antenna Polarisation: Vertical and Horizontal
 Modulation: 1kHz,80% Amp. Mod,1% increment


7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21 °C Humidity: 53 % RH Atmospheric Pressure: 1010 mbar

Test Mode: a:normal working mode.
 b:idle mode.

7.3.2 Test Setup Diagram



7.3.3 Test Results:


Frequency	Level (V/m)	EUT Face	Dwell time	Result / Observations
80MHz-1GHz	3	Front	2s	A
80MHz-1GHz	3	Back	2s	A
80MHz-1GHz	3	Left	2s	A
80MHz-1GHz	3	Right	2s	A
80MHz-1GHz	3	Top	2s	A
80MHz-1GHz	3	Underside	2s	A

Results:

A: No degradation in the performance of the EUT was observed.

8 Photographs

8.1 Radiated Disturbance(30MHz-1GHz) Test Setup



8.2 Electrostatic Discharge Test Setup




8.3 Radiated Immunity(80MHz-1GHz) Test Setup



8.4 EUT Constructional Details





--End of Report--